

Date: \_\_\_\_\_

Job Name: \_\_\_\_\_

Designation: \_\_\_\_\_



## DS SERIES Mini-Distribution Centres

The DS Series distribution panels streamline installation by conventional splitters.

125A 600V rated Main disconnect;  
up to 4 feeder breakers.

### Specifications

- CSA 3R Cold Rolled Steel Enclosure
- 30" H x 25" W x 8.75" D
- Wall Mount
- Single Hinged Door, double pad locking latches.
- ASA 61 Grey Powder Coat Finish
- Main Breaker
- CSA SPE1000 Approved
- Terminal Blocks

### Options

- Voltage Indicator
- Aluminum Enclosure
- Metering

### Part Number Configuration

**3 - DS - 1 - 2 - 7045 -**

<b>Phase</b>	<b>Model</b>	<b>Main Breaker</b>	<b>Factory Installed Secondary Breakers</b>
Blank - Single Phase 3 - Three Phase	MDS Series	1 - 125A	1-4
<b>Secondary Brkr Amps</b>	<b>Options</b>		
List amperages up to 4 eg. 1-70A, 2-45A, 1-30 = <b>70454530</b>	Blank - No Options    AL - Aluminum Encl.    M - Metering    V - Voltage Indicator		