

Date: _____

Job Name: _____

Designation: _____



SEK-BC SERIES

Main Distribution Centres

The SEK-BC Series outdoor kiosks are designed and built in compliance with BC Hydro's latest standards for outdoor secondary services applications.

Single Phase up to 600A,
Three Phase up to 1600A.

Specifications

- Marine Grade CSA 3R Aluminum
- Pad Mount
- Double Doors with 3 Point SS Handle and Latch
- Removable Lifting Ears
- ASA 61 Grey Powder Coat Finish
- Main Breaker
- External Meter Base
- BCH Rated Wireway, Metering Section, Sealing Provisions
- Line and Load Lugs Included

Options

- LED Light
- Heater
- Receptacle
- Fan
- Stainless Steel
- Insulation
- Custom Power Coat
- Internally Mounted Meter with Viewing Window (BCH Approval Required)

Phase	Amp	Voltage	H	W	D
1	400-600	120/240	75"	56"	20"
3	400-1200	120/208/600	75"	56"	20"
3	1600	120/208/600	75"	76"	20"

Part Number Configuration

SEK-BC - 800 - 3 - C -

Model	Amperage	Phase	Voltage
SEK-BC Series	400 1000 600 1200 800 1600	1 - Single Phase 3 - Three Phase	A - 120/240 B - 120/208 C - 347/600

Options

- | | | | |
|---------------------------|-----------------------|---------------------------|-----------------------------|
| Blank - No Options | R - Receptacle | I - Insulation | IM - Internal Meter |
| L - LED Light | F - Fan | CC - Custom Colour | SS - Stainless Steel |