POWERC © **NNECT**

Date: _____

Job Name:_____

Designation:_____

SEK-D-BC SERIES

The SEK-D-BC Series outdoor kiosks are designed and built in compliance with BC

breakers per customer requirements.

Single Phase up to 600A, Three Phase up to 1600A.

Hydro's latest standards for outdoor secondary services applications. SEK-D includes load side

Main Distribution Centres

Specifications

- Marine Grade CSA 3R Aluminum
- Pad Mount
- Double Doors with 3 Point SS Handle and Latch
- Removable Lifting Ears
- ASA 61 Grey Powder Coat Finish
- Main Breaker
- External Meter Base
- BCH Rated Wireway, Metering section, Sealing Provisions
- Line and Load Lugs Included
- Load Breakers Per Requirement

Options

- LED Light
- Heater
- Insulation
- Custom Power Coat
- Receptacle
- Fan
- Stainless Steel
- Internally Mounted Meter with Viewing Window
- (BCH Approval Required)

Phase	Amp	Voltage	Н	W	D
1	400-600	12/240	75″	56″	20″
3	400-1600	120/208/600	75″	76″	20″

Part Number Configuration

SEK-D-BC	- 800 - 3	3 - C -	7045 -

Model	Amperage		Phase	Voltage	
SEK-D-BC Series	400 1000 600 1200 800 1600		ingle Phase hree Phase	A - 120/240 B - 120/208 C - 347/600	
Secondary Brkr Amps					
List amperages up to 4 eg. 1-70A, 2-45A, 1-30 = 70454530	Options				
	Blank - No Options L - LED Light	R - Receptacle F - Fan	I - Insulation CC - Custom Co	IM - Internal Meter Nour SS - Stainless Steel	