

The SEK-D-BC Series

Project: _____

Contact: _____

Service Entrance Kiosk

The SEK-D-BC Series outdoor kiosks are designed and built in compliance with BC Hydro's latest standards for outdoor secondary services applications. SEK-D includes load side breakers per customer requirements.



*Image shown is representative of the product series and may not reflect the exact model.

Product ID

SEK - XX - X - XXX - X - X

Variant Components

▶ PROV.	▶ DIST. PANEL & ENCL	▶ AMPERAGE	▶ PHASE	▶ VOLTAGE
BC CA	X = No D = Yes	200 400 600 800 1000 1200 1600 2000	1 - 1PH (200 to 600) 3 - 3PH (200 to 2000)	A - 120/240 B - 120/208 C - 347/600 D - 277/480

Specifications and Standard Features

- Service Entrance Main Breaker
- ANSI 61 Powder Coat Finish
- Pad Mount
- Removable Lifting Ears
- Double Doors with 3 Point SS Handle and Latch
- Compliant with BCH Metering Standards: Metering section, Utility Wireway, Customer only Access 3rd Door
- Marine Grade CSA 3R Aluminum Construction
- Internal heater with Thermostat
- Circulating Fans
- Insulated Roof
- SPE 1000 Certified

Specifications and Standard Features

- LED Light(s)
- Maintenance Receptacle(s)
- Stainless Steel Construction (304 or 316)
- Fully Insulated
- Load Breakers as Required
- Double sided Enclosure for Various Distribution, Communication and Custom Requirements
- Custom Powder Coat
- Internally Mounted Meter with Viewing Window
- Marine Grade CSA 4X Aluminum Construction
- Distribution Panels as Required

Phase	Amps	Voltage	H	W	D
1	400-1600	120/240	80"	56"	20"
3	400-1600*	120/208, 277/480, 347/600	80"	76"	20"

* 90" for Dist.